



HUSQVARNA R 115C

Compact and user-friendly Rider with 95 cm Combi cutting deck. Suitable for homeowners who want an efficient and multipurpose ride-on mower that can handle mowing around obstacles like trees, bushes and flower beds. The articulated steering system and front-mounted cutting deck means intuitive operation, excellent mowing accessibility and great overview of your working area. Pedal-operated hydrostatic transmission, easy-access controls and automatic blade engagement, makes mowing a pleasure. The rear-wheel drive ensures extra traction when mowing in slopes. This Rider can do so much more than cutting your lawn. Thanks to attachments such as snow blade, trailer, moss rake and spreader, it can maintain your garden all year round.



Combi cutting deck

The Combi cutting deck offers the versatility of two different cutting systems. Choose between BioClip® for lawn fertilisation and rear ejection for efficient mowing on areas with higher and rougher grass.



Front-mounted cutting deck

Front-mounted cutting deck for excellent accessibility into corners and under bushes, park benches etc.

Articulated steering

The articulated steering gives excellent manoeuvrability and facilitates driving around obstacles such as trees and bushes.



Two-blade cutting deck

Robust cutting deck with two blades and angled position for optimum trimming on the left hand side. For smallest uncut circle, turn left.

FEATURES

- Articulated steering for excellent manoeuvrability
- Front-mounted deck for optimum accessibility
- Combi cutting deck
- Two-blade cutting deck
- Efficient rear-wheel drive system
- Comfortable driver's position
- Compact design for operation in tight spaces
- External fuel cap for easy refueling
- Pedal-operated hydrostatic transmission
- Easy-access controls for user comfort
- Automatic blade engagement
- Single-lever cutting height adjustment
- BioClip® mode for frequently cut areas
- Rear ejection cutting mode for rougher areas
- Equally sized wheels for a comfortable ride
- Engine behind driver for better overview
- Tilting hood makes maintenance quick and easy
- Easy fuel level check by transparent fuel tank
- Pivoting rear axle for maximum traction
- Cup holder for refreshments while mowing

Technical specifications

BATTERY	
Battery capacity	21 Ah
Battery manufacturer	Global
Battery pack weight	7 kg
Battery type	Lead/Acid
Battery voltage	12 V
DIMENSIONS	
Base machine, height	108 cm
Base machine, length	229 cm
Base machine, width	99 cm
Ground clearance	105 mm
Tyre dimensions, front	170/60-8
Tyre dimensions, rear	170/60-8
Weight	208 kg
Wheelbase	84.5 cm
Article gross weight	260000 g
Article net weight	208000 g
Cutting height max	75 mm
Cutting height min	25 mm
Cutting height steps	5
Cutting width	95 cm
ENGINE	
Cylinder displacement	500 cm ³
Cylinders	1
Electric start	Yes
Engine cooling	Air
Engine lubrication type	Splash
Engine name	PowerBuilt AVS
Motor/engine manufacturer	Briggs & Stratton
Motor/engine model	4145
Spark plug	EMS Q, Champion XC92YC
EQUIPMENT	
Air filter type	Cartridge
Ball bearing front wheels	Yes
Blade engagement	Automatic
Blades	2 pcs
Consumer product type	Riders
Cutting deck type	Stamped
Drive method	Pedal-operated
Foldable seat	Yes
Frame construction type	Steel tube
Powder-coated cutting deck	Yes
Seat manufacturer	SEAT
Seat suspension	Yes
Serie	100-serie
Technical Platform	R100-series
Wheelbase	84.5 cm
LUBRICANTS	
Engine lubrication type	Splash
Fuel consumption	537 g/kWh
Fuel tank volume (with reserve)	7 l
Fuel tank volume	7 l
Power/fuel type	Gasoline
Oil capacity	1.4 l
Oil filter	No
Oil type	SAE 10W30
SOUND AND NOISE	
Sound power level, guaranteed (LWA)	99 dB(A)

Technical specifications	
Sound power level, measured	99 dB(A)
Sound pressure level at operators ear	85 dB(A)
VIBRATIONS	
Vibration level seat	0.2 m/s ²
Vibration level steering wheel	1.6 m/s ²
EMISSION DATA	
Exhaust emissions (HC+NOx w/o catalytic converter)	5.6 g/kWh
EMISSION DATA EU	
Exhaust emissions (CO2 EU V)	794 g/kWh
PACKAGING	
Packaged weight	260 kg
Packaging height	980 mm
Packaging length	2310 mm
Packaging volume	2303,14 dm ³
Packaging volume	2,535 m ³
Packaging width	1120 mm
Packaging, gross weight	64 kg
Quantity in Master pack	1