



HUSQVARNA 340i

Powerful and versatile battery chainsaw Husqvarna 340i is a powerful and light, versatile, battery-powered chainsaw with great cutting capacity for all-round use like felling, pruning, cutting firewood or carpentry. Great manoeuvrability thanks to the saw's narrow body which keeps the centre of gravity close to the handles. Low vibration and noise levels and smart user interface with easily visible battery status on the handle. Tool-less or standard chain tensioning. Easy to use with both internal or backpack battery.

Ergonomic design

The narrow saw body, high centre of gravity and flat underside make the saws handy to work with.



Efficient brushless motor

Our in-house developed, advanced brushless motor is 25 % more efficient than a standard brush motor. This means that the motor provides a high and consistent torque.

savE™

Choose between normal or savE™ mode, depending on conditions, for maximum power or maximum runtime. Either way, you'll always get a perfect result.

Tool less chain tensioning

Quick and easy chain tensioning and assembling of the bar and the chain without using any tools.



FEATURES

- Choose savE™ mode for maximum runtime
- In-house developed brushless motor provides a high and consistent torque.
- Ergonomic design, easy to work with
- Tool less chain tensioner
- Key pad
- Fast, smooth cutting
- The flip-up tank cap is easy to open.
- Allows you to quickly switch the same battery between different product applications and keep working.
- Low maintenance and less downtime
- Gear up for nonstop operation
- Increased safety, inertia activated chain brake
- High power equally to petrol performance

Technical Specifications	
BATTERY	
Battery type	Li-Ion
Battery voltage	36 V
CAPACITY	
Chain speed at max power	20 m/s
DIMENSIONS	
Article gross weight	4059 g
Article net weight	3663 g
Bar length (inch)	14"
Weight (excl. battery and cutting equipment)	2.8 kg
EQUIPMENT	
Bar mount type	Small
Chain type	S93G
Chainsaw sub-group	Part time use chainsaws
Handle type	Standard
Pitch	3/8" mini
Sprocket type	Spur 6
LUBRICANTS	
Oil pump capacity Max	11 ml/min
Oil pump type	Automatic
Oil tank volume	0.2 l
Power/fuel type	Battery
MATERIALS	
Master pack: Paper + Cardboard	0 g
Metal total	0 g
Paper + Cardboard total	0 g
PE total	0 g
PET total	0 g
Plastic foil	0 g
Plastic rigid	0 g
Plastic total	0 g
PS/EPS/HIPS total	0 g
PACKAGING	
Packaging height	280 mm
Packaging length	490 mm
Packaging width	250 mm
Quantity in Master pack	1
SOUND AND NOISE	
Sound power level, guaranteed (LWA)	101 dB(A)
Sound power level, measured	99 dB(A)
Sound pressure level at operators ear	88 dB(A)
VIBRATIONS	
Daily Vibration (Aeqv)	3.2 m/s ²
Daily Vibration Exposure (A8)	2.2 m/s ²
Daily Vibration Time (Time factor)	3.7 h
Equivalent vibration level (ahv, eq) front handle	3.2 m/s ²
Equivalent vibration level (ahv, eq) rear handle	3.2 m/s ²